



P100 SIP IP Phone

Soundwin Network design graceful P100 VoIP phone with high voice quality in order to provide overall VoIP solutions to enterprises. Together with Soundwin IP PBX series (iPBX/WiPBX/IPX200/IPX400), P100 SIP IP Phone is the best choice for enterprises. Users can configure personal IP phone via easy-to-configure web interface

Key

- 10 speed dialing hotkeys
- 4 ways navigation keys
- Voice message
- Volume control key
- Alphanumerical key
- Function Keys
 - Phonebook
 - Redial
 - DND
 - Hold
 - Transfer
 - Conference
 - Forward
 - Delete
 - Mute

IP Specifications:

- SIP v2.0 (rfc3261)
- IP/TCP/UDP/RTP/RTCP/ICMP/ARP/RARP/SNTP
- TFTP/FTP/DHCP/DNS/SNTP Client
- PPPoE/ Static/ DHCP IP Assignment
- NAT Transversal -STUN
 - Media Relay
- DTMF function :
 - In-Brand DTMF
 - Out-of-Band DTMF (RFC2833)
 - SIP Info
- VLAN Setting Support

Call Features

- Call redialing- call back the last number dialed
- DND support
- Call On-Hold-on hold current call
- Call Transfer- attended & blind transfer
- Call Forwarding- forwarding by demand or duration
- Call Waiting

Voice Quality

- VAD: Voice activity detection
- CNG: Comfortable noise generator
- ACE: Acoustic echo canceller
- Jitter Buffer

Codec

- G.711: 64k bit/s (PCM)
- G.723.1: 6.3k / 5.3k bit/s
- G.726: 16k / 24k / 32k 40k bit/s (ADPCM)
- G.729A : 8K bit/s (CS-ACELP)
- G.729B: adds VAD & CNG to G.729

LCD Display

- LCD with 2*16 Dot matrix
- Caller ID support
- Displays simultaneous calls
- Date & Time display

General Specification

- Dimensions: 230x207x950 mm
- Weight: 0.819kg
- 12V DC adapter, supplied locally at the desktop using the included AC to DC power supply

Gateway Technology Development Co. Ltd.

Tel (Hong Kong) : 852-2779-3000

Tel (China) : 86-755-8366-0255

Email : sales@hkgateway.com